




เครื่องปรับอากาศ “แคเรียร์”



40GKX/38RE Series

DX Coil Cassette Type

13,000-48,000 BTUH




40GKX / 38RE Series

Flexible and Optimised Air Distribution



The pleasing new grille profile, designed and patented by Carrier, permits increased air throws without creating draughts for the occupants.



* Fresh air intake, for ambient air Renewal, and additional outlet grille, to air condition an adjoining room.

In addition to the high air distribution performance, the Alpine Cassette allows the introduction of up to 10% of fresh air. A benefit that facilitates permanent renewal of the ambient air and consequently improves its quality.

This exclusive technology is combined with motorised louvers which offer six selectable air flow directions, continuous air sweep or automatic positioning.

The return air filtered at the centre of the grille and can be distributed on four, three or two sides.

By limiting the air distribution to three sides, it is possible to add a branch duct and second outlet grille of air condition an adjoining room.



◀ WIRELESS REMOTE CONTROL

Specifications

Description			Cassette Type							
Model	Outdoor		38RE-G2							
			012	018	024	033	036	036BSC	036SC	048SC
	Indoor		40GKX							
			012	018	024	036	036	036	036	048
Cooling Capacity*	Btuh.		13,307	19,107	25,249	33,096	36,167	36,167	36,167	48,000
	Watt.		3,900	5,600	7,400	9,700	10,600	10,600	10,600	14,068
Power Supply	V/PH/h.Z.		220/1/50				380/3/50			
Power Input	Watt.		1,230	1,767	2,334	3,129	3,419	3,419	3,419	4,538
EER.	Btuh/Watt.		10.82	10.82	10.82	10.58	10.58	10.58	10.58	10.58
COP.	Watt/Watt		3.17	3.17	3.17	3.10	3.10	3.10	3.10	3.10
Current (RLA)**	Amp		5.6	8.1	10.7	14.4	15.7	15.7	6.40	8.49
Indoor Air Circulation	Cfm		390/350/320	410/370/330	530/450/330	740/650/570	740/650/570	740/650/570	740/650/570	970/830/680
	L/s		183/167/152	194/175/156	250/213/189	350/305/270	350/305/270	350/305/270	350/305/270	460/390/320
Dimension (outdoor)	Height	mm.	585	635	635	740	890	890	890	890
	Width	mm.	855	905	905	905	1,095	1,095	1,095	1,095
	Depth	mm.	280	330	330	330	435	435	435	435
Dimension(indoor)	WxLxH	mm.	720x720x298				960x960x298			
Ceiling Open	WxL	mm.	660x660				900x900			
Net weight	Outdoor	kg.	43	50	70	78	89	90	90	118
	Indoor	kg.	20	21.5	25	43	43	43	43	45
Refrigerant			R-22							
Connections	Liquid	inch.	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8
		mm.	6.35	9.53	9.53	9.53	9.53	9.53	9.53	9.53
	Suction	inch.	1/2	5/8	5/8	3/4	3/4	3/4	3/4	7/8
		mm.	12.70	15.88	15.88	19.05	19.05	19.05	19.05	22.23
Condensate Drain	inch.	1								
	mm.	25.40								
Type of Compressor			Rotary	Rotary	Rotary	Rotary	Rotary	Scroll	Scroll	Scroll

* COOLING CAPACITY BASED ON ENTERING AIR TEMP.80 °F.DB/67 °F.WB, AMBIENT TEMP.95 °F.DB
** RLA:RATED LOAD AMPERE

Carrier reserves the right to make changes in specifications without prior notice.
บริษัทฯ ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า



◀ 38RE-G2 Series

บริษัท แคนเรีย (ประเทศไทย) จำกัด
ชั้น 14-15 อาคารเนชั่น ทาวเวอร์
46/63-74 ถ.บางนา-ตราด กม. 4.5
บางนา กรุงเทพฯ 10260
โทร. 0-2751-4777 แฟกซ์: 0-2751-4778

Carrier (Thailand) Ltd.
14-15th Fl., Nation Tower,
46/63-74 Bangna-Trad Road Km. 4.5, Bangna,
Bangkok 10260 Thailand
Tel.: 0-2751-4777 Fax: 0-2751-4778



YOUR CARRIER MAN :